



## APC Notebook Surge Protector for AC, phone and network lines, 2 pin connection, 100-240V

**Part Number:** PNOTEPROC8



### Output

Number of Outlets	1
Receptacle Style	IEC 320-C8

### Input

Nominal Input Voltage	120V
Input Frequency	50/60 Hz
Input Connections	IEC 320 C8
Maximum Line Current per phase	4A

### Surge Protection and Filtering

Surge energy rating	180 Joules
Peak Current Normal Mode	6.50 kAmps
NM Surge Response Time (ns)	1 ns
Data Line Protection	RJ-11 Modem/Fax protection (two wire single line),RJ45 10/100 Base-T Ethernet protection
Let Through Voltage Rating	< 330

### Physical

0.20 lbs. (0.10 kg)	
1.08 inches (27 mm)	
Maximum Width	1.26 inches (32 mm)
Maximum Depth	3.86 inches (98 mm)
Shipping Weight	0.42 lbs. (0.20 kg)
Shipping Height	2.60 inches (66 mm)
Shipping Width	6.22 inches (158 mm)
Shipping Depth	7.56 inches (192 mm)
Master Carton Units	12.00
Master Carton Dimensions (Length x Width x Height)	16.5 X 11.5 X 8.3 inches
Master Carton Weight	6.00 lbs.
Color	Silver
Units per Pallet	480.00

## Environmental

Operating Environment	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	0%
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	5 - 113 °F (-15 - 45 °C)
Storage Relative Humidity	0%
Storage Elevation	0-30000 feet (0-9000 meters)

## Conformance

Regulatory Approvals	CSA,FCC Part 68,NOM,UL Listed
Standard Warranty	Lifetime
Equipment protection policy	Lifetime : \$75000
UL 1449 TVSS Rating	700V
Environmental Compliance	RoHS

\*Except where noted, all prices are Estimated Resale Price (ERP) - Without Tax/VAT. Pricing in other locations and sites may vary.

[Copyright](#) © American Power Conversion Corp., all rights reserved

For more information or to order this product,  
please contact us at:  
[sales@jackrabbit.com](mailto:sales@jackrabbit.com)



**jackrabbit.com**  
Ready-to-Use Technology for Small Businesses  
Since 1982

*Jackrabbit Microwave - Poway, CA USA*